


MTP-MDC 8-fiber Duralino fanout - Simplex

Basic characteristics

- ▲ Constructed of high-quality fiber optic cable and components
- ▲ Female/Male type of MTP® connector
- ▲ Fan-out legs are protected by 2,0mm simplex tubing with Aramid yarns
- ▲ MTP® PRO connector optional



Applications

- ▲ Data center
- ▲ Storage Area Network
- ▲ Short distance connections within a single rack or cabinet

Temperature range

Indoor controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	LSZH	
Cable construction	Round double jacket cable	
Outer diameter	3.0/4.5mm	
Fiber count	12	
Fiber type	SMF OS2 MMF OM3/OM4/OM5	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C
CPR	C _{ca} -s1a, d1, a2	

Connector parameters

	MTP® /MTP® PRO SM/MM	MDC Sr. SM/MM
Compliance	US ConneC standard	Telcordia GR-326
Color of housing	Green (APC)	Blue (UPC)/Green(APC)
	Aqua / Magenta / Lime Green	Aqua / Magenta / Lime Green
Color of boot	Black	Black
Polish	Angled (APC)	Flat SM (UPC) / Angled (APC)
	Flat	Flat MM (PC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,35dB (@1310/1550nm/@850/1300nm)	<0,25dB (@1310/1550nm/@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>50dB(APC)/>20dB (@1310/1550nm/@850/1300nm)	>50dB(UPC)/>65dB(APC)/>20dB (@1310/1550nm/@850/1300nm)

MTP-MDC 8-fiber Duralino fanout - Simplex

Identification

Traceability label with unique serial number on both ends of cable assembly.

Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box. Longer lengths coiled on cardboard reel.

*MTP is a registered trademark of US Conec, Ltd

*Specifications are subject to change without notice

*Cable with PVC outer jacketed material available on demand

For more information contact our sales team at sales@sylex.sk