

FTTA DISTRIBUTION BOX Size L – 48 Fibers

Basic characteristics

- Robust outdoor distribution box
- Integrated pole bracket for various shapes of poles
- Easy to mount on wall or pole
- Supports 24 RRHs
- Variable grommet system

Benefits

- Increased durability, impact protection
- Equipped with LCD adapters
- Secure fixation of feeder, drop cables

Applications

- 🔺 FTTA
- ▲ 5G networks
- Telecom

Temperature range

Outdoor environment (-40°C/+70°C)

Box parameters	
	FTTA distribution box L - 48 Fibres
Dimensions	427 × 290 × 132 mm
Number of LC adapters	24x LC Duplex
Number of RRHs	Up to 24 RRH
Cable sizes	Compatible with cables with OD 3–8mm
Weight	3kg
Colour of box	Light grey RAL 7035
Ingress protection	IP65
Impact resistance	IK10
Flammability degree	UL94 - V0
Material	PC/ASA
Identification	
Traceability I	abel with unique serial number on each box.

Packaging

Each assembly in cardboard box.

* Specifications are subject to change without notice

For more information, contact our sales team at sales@sylex.sk

Release date: 24th of May, 2022 | Version: 00 | Revision: 00

SYLEX s.r.o. | Mlynské luhy 31 | 821 05 Bratislava | Slovak Republic | Email: sales@sylex.sk | www.sylex.sk

FTTA Solution