

FTTA DISTRIBUTION BOX Size S – 12 Fibers

Basic characteristics

- Robust outdoor distribution box
- Integrated pole bracket for various shapes of poles
- Easy to mount on wall or pole
- Supports 6 RRHs
- Variable grommet system

Benefits

- Increased durability, impact protection
- Equipped with LCD adapters
- Secure fixation of feeder, drop cables

Applications

- 🔺 FTTA
- ▲ 5G networks
- Telecom

Temperature range

Outdoor environment (-40°C/+70°C)

Box parameters	
	FTTA distribution box S - 12 Fibres
Dimensions	252 × 150 × 85 mm
Number of LC adapters	6x LC Duplex
Number of RRHs	Up to 6 RRH
Cable sizes	Compatible with cables with OD 3–8mm
Weight	1kg
Colour of box	Light grey RAL 7035
Ingress protection	IP65
Impact resistance	IK10
Flammability degree	UL94 - V0
Material	PC/ASA
Identification	
Traceability I	label with unique serial number on each box.
Developments a	

Packaging

Each assembly in cardboard box.

* Specifications are subject to change without notice For more information, contact our sales team at sales@sylex.sk

Release date: 24th of May, 2022 | Version: 00 | Revision: 00 SYLEX s.r.o. | Mlynské luhy 31 | 821 05 Bratislava | Slovak Republic | Email: sales@sylex.sk | www.sylex.sk

