# sylex® FIBER OPTICS

## SC 2U patch panel – with adapters

### Basic characteristics

▲ Width 19"
▲ Height 2U
▲ Space for 4 back plates ready for Duralino fanout® fixation
▲ With adapters



### Benefits

▲ Exchangeable front panels and back plates
▲ Adjustable depth of position in rack
▲ 48/72x SC simplex adapters and 48x SC duplex adapters

### Applications

▲ Telecom/Datacom
▲ LAN/WAN Networks

| Temperature range | | |
|---|---|---|
| Indoor controlled environment (-10°C /+60°C) | | |
| **Parameters** | | |
| Dimensions | | 482 x 251x 88 mm (2U) |
| Material | | powdered coating steel |
| Colour | | light gray RAL7035 |
| Capacity | | up to 96 fibers |
| Cable entry ports | grommet/gland | 4x PG13,5/M20 or 8x PG7/M12 |
| | Duralino® fanout | 4x Duralino fanout® size XL/L or 8x Duralino fanout® size S |
| **Identification** | | |
| Label with unique serial number. | | |
| **Packaging** | | |
| Each patch panel in cardboard box, bulk pack on palette. | | |

\* Specifications are subject to change without notice

**For more information contact our sales team at sales@sylex.sk**

**Release date:** 31st of March, 2021 | **Version:** 01 | **Revision:** 00
**SYLEX s.r.o.** | Mlynské luhy 31 | 821 05 Bratislava | Slovak Republic | **Email:** sales@sylex.sk | **www.sylex.sk**
1/1