

## VERTEX 1U 19" High-density panel, 12-module capacity

## **Basic characteristics**

- ▲ Height 1U
- ▲ Space for fixation of Duralino fanout®
- Saddles on both sides for incoming cables
- Cable management between all modules



Adaptor type	Connector type	No. of modules	Connections
LC DX adaptor	LC SX/DX or Unitboot	12	144

## **Benefits**

- Exchangeable types of cassettes
- Adjustable depth of position in rack
- Removable top cover for easier access

## **Applications**

- DataCentre cabling
- Telecom/Datacom
- ▲ LAN/WAN Networks

Temperature ran	ge			
	Indoor controlled environme	nt (-10°C / +60°C)		
Parameters				
Dimensions		443 x 436x 44 mm (1U)		
Material		Powder coated steel		
Colour	Deep black RAL9005			
Capacity		12x VERTEX modules		
Cable entry ports	grommet/gland	3x PG13.5/M20 or 6x PG7/M12		
	Duralino® fanout	3x Duralino fanout® size L / XL or 6x Duralino fanout® size S		
Identification				
Label with unique serial number.				
Packaging				
	Each patch panel in cardboard bo	x, bulk pack on palette.		
	<u> </u>	·		

<sup>\*</sup> Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk