


CONNECTION TABLE	
MTP	SN
1	1 WIDE KEY
2	2 WIDE KEY
3	3 WIDE KEY
4	4 WIDE KEY
5	
6	
7	
8	
9	4 NARROW KEY
10	3 NARROW KEY
11	2 NARROW KEY
12	1 NARROW KEY



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - SN: OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
SN: OS2 - IL<0.25dB, SN/UPC - RL>50dB, 1310nm & 1550nm

MTP: OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm
MTP: OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm

IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - MTP VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35
SN VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326 (Singlefiber connector)
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished)
- 5 - ASSEMBLY PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER, DATE OF PRODUCTION AND ASSEMBLY LENGTH

ORDERING CODE

X08X-X86-xxx-Q

- xxx cable length [050 = 50m, 001 = 1m]
- 6 1.6mm tubing
- 8 SN 1.6mm
- F MTP(F) 12F, M MTP(M) 12F,
J MTP(F) PRO 12F, P MTP(M) PRO 12F
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 08 8F
- F fanout, H fanout with grommet*
- * SHOWN TRUNK VERSION WITH GROMMET [H]

REVISION-DATE: A - 26.03.2021	CHANGE:	DRAWN BY, DATE: M.Ruzbarsky 2021/03/26	TITLE: 8f MTP - SN Fanout		
New drawing		CHECKED BY, DATE: L.Miskerik			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: Matus/Smelh.	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE:	CHANGE:	PRODUCT NUMBER: XXXX-XXX-xxx	DRAWING NUMBER: 1-W-8381_1_A	SHEET NO. 1 of 1	
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED			SIZE A3