


CABLE DATASHEET



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4 - IL<0.6dB , 850nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (APC polished)
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (FLAT polished)
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-0011](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)

ORDERING CODE

P48X-XXX-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- X - Polarity on customer demand
- 2 MTP(F) 48F, 3 MTP(M) 48F
- 2 MTP(F) 48F, 3 MTP(M) 48F
- 3 OM3, 4 OM4
- 48 48F
- P Trunk

REVISION-DATE: A - 04.06.2019	CHANGE:	DRAWN BY, DATE: P. Gašpár 2019/06/04	TITLE: 48f 1xMTP - 1xMTP Trunk		
New drawing		CHECKED BY, DATE: Pavlov/Matúš			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I.Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:	PRODUCT NUMBER: P48X-XXX-xxx	DRAWING NUMBER: -	SHEET NO. 1 of 1	
A			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED		
			SIZE A3		