



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm
- IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
APC POLISHED END FACE GEOMETRY ACCORDING TO IEC 61755-3-31
FLAT POLISHED END FACE GEOMETRY ACCORDING TO IEC 63267-3-31
- 5 - ASSEMBLY PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.
- 6 - CABLE LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER, DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)

ORDERING CODE

SSSX-xxX-xxx

- xxx cable length [050 = 50m, 001 = 1m] *
- A - Polarity A, B - Polarity B, C - Polarity C
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- S SPECIAL PRODUCTS

* Typical lengths up to 5 meters. Other versions upon prior consultation.

REVISION-DATE: A - 30.06.2021	CHANGE:	DRAWN BY, DATE: P.Gaspar 2021/06/30	TITLE: 12f 1xMTP - 1xMTP Armored Patch Cable		
NEW DRAWING		CHECKED BY, DATE: L.Miskerik 2021/06/30			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: Matus/Smelh. 2021/06/30	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE:	CHANGE:	PRODUCT NUMBER: XXX-XXX-xxx-X	DRAWING NUMBER: 1-W-8601_1_A	SHEET NO. 1 of 1	
		A	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED		
			SIZE A3		