



NOTES :

- 1 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 2 - OM1, OM3, OM4 - IL<1.5dB, RL>20dB, 850nm & 1300nm  
OS2 - IL<1.0dB, RL>32dB, 1310nm & 1550nm
- 3 - VISUAL ASPECT (INNER FERRULE) CHECK ACCORDING TO IEC 61300-3-35.  
END FACE GEOMETRY (INNER FERRULE) ACCORDING TO TELCORDIA GR-326
- 4 - ASSEMBLY COILED ON PLASTIC DRUM,  
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-8001](#)
- 5 - CABLE LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 6 - TRACEABILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,  
DATE OF PRODUCTION AND ASSEMBLY LENGTH

ORDERING CODE

**RXXX-66A-xxx**

- xxx cable length [050 = 50m, 001 = 1m]
- A - 5.5mm Tactical round cable
- 6 PRO BEAM Jr. Plug
- 6 PRO BEAM Jr. Plug
- 9 OS2, 1 OM1, 3 OM3, 4 OM4
- 02 02F, 04 04F
- R MIL/DEF PRODUCT

REVISION-DATE: A - 07.04.2020	CHANGE:	DRAWN BY, DATE: P. Gašpár 2020/04/16	TITLE: 02/04f PRO BEAM Jr. Plug Patch Cable		
NEW DRAWING		CHECKED BY, DATE: Pavlov/Matúš 2020/04/16			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I.Brestovanská 2020/04/16	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE:	CHANGE:	PRODUCT NUMBER: RXXX-66A-xxx	DRAWING NUMBER: -	SHEET NO. 1 of 1	
		<b>A</b> THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED	SIZE A3		