



4 X
1 2
FIBERS

-
- other connectors not shown
-

4 X
1 2
FIBERS

-
- other connectors not shown
-

NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm
LC/UPC - RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-0011](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - PULLING SYSTEM ON ONE SIDE IS PART OF THE ASSEMBLY (NOT SHOWN)
- 8 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,
DATE OF PRODUCTION AND ASSEMBLY LENGTH

ORDERING CODE

X48X-XXU-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- U 2.0mm unitube tubing
- AA LC/APC-LC/APC, LL LC/PC-LC/PC *
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 48 48F
- T trunk, G trunk with grommet **

* OTHER CONNECTOR TYPES ON REQUEST
** SHOWN TRUNK VERSION WITH GROMMET [G]

REVISION-DATE: A - 26.06.2019 CHANGE: New drawing	DRAWN BY, DATE: P. Gašpár 2019/06/26	TITLE: 48f LCD Uniboot-LCD Uniboot Duralino Trunk		
REVISION-DATE: CHANGE: 	CHECKED BY, DATE: Pavlov/Matúš 2019/06/26	APPROVED BY, DATE: I.Brestovanská 2019/06/26	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED
REVISION-DATE: X - DD.MM.YYYY CHANGE: 	APPROVED BY, DATE: I.Brestovanská 2019/06/26	PRODUCT NUMBER: X48X-XXU-xxx	DRAWING NUMBER: 1-S-7157_1_A	SCALE: NO SCALE
			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED	SHEET NO. 1 of 1
			SIZE A3	