



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4 - IL<0.25dB , RL>30dB , 850nm & 1300nm
OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm
LC/UPC - RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - CROSS AND STRAIGHT CONNECTION ACCORDING TO SYLEX STANDARD [1-S-7307](#)

C2XX-XXX-XXX-X

- S STRAIGHT, LEAVE EMPTY FOR CROSS
- xxx cable length [050 = 50m, 001 = 1m]
- U UNIBOOT CONNECTOR,
P UNIBOOT CONNECTOR w PUSH-PULL
- L LC/UPC, A LC/APC
- L LC/UPC, A LC/APC
- 9 OS2, 3 OM3, 4 OM4
- 2 1.8mm
- 2 DUPLEX
- C Cord

REVISION-DATE: A - 11.05.2023	CHANGE:	DRAWN BY, DATE: M.Ruzbarsky 2023/05/11	TITLE: 2f LC Uniboot Jumper		
New drawing		CHECKED BY, DATE: L.Miskerik			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: Matus/Smelh.	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE:	CHANGE:	PRODUCT NUMBER: C2XX-XXX-xxx	DRAWING NUMBER: 1-S-7402_1_A	SHEET NO. 1 of 1	
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED			SIZE A3