

SAT-01 Single Axis Tiltmeter
Measurement range -5deg. to +5deg., Temperature range -20°C to +60°C

Ordering information			Installation information			
WL configuration	WL type	Nominal WL @ 0deg. @ 22,5°C (after production)	(WL @ -5deg. @ -20°C)	WL @ 0deg. @ 22,5°C	WL @ +5deg. @ +60°C	WL @ +5deg. @ -20°C
A	Tilt 1	1 513,0nm	1 513,9nm	1 513,0nm	1 512,0nm	1 511,1nm
	Tilt 2	1 517,0nm	1 515,1nm	1 517,0nm	1 518,8nm	1 517,9nm
B	Tilt 1	1 523,0nm	1 523,9nm	1 523,0nm	1 522,0nm	1 521,1nm
	Tilt 2	1 527,0nm	1 525,1nm	1 527,0nm	1 528,8nm	1 527,9nm
C	Tilt 1	1 533,0nm	1 533,9nm	1 533,0nm	1 532,0nm	1 531,1nm
	Tilt 2	1 537,0nm	1 535,1nm	1 537,0nm	1 538,8nm	1 537,9nm
D	Tilt 1	1 543,0nm	1 543,9nm	1 543,0nm	1 542,0nm	1 541,1nm
	Tilt 2	1 547,0nm	1 545,1nm	1 547,0nm	1 548,8nm	1 547,9nm
E	Tilt 1	1 553,0nm	1 553,9nm	1 553,0nm	1 552,0nm	1 551,1nm
	Tilt 2	1 557,0nm	1 555,1nm	1 557,0nm	1 558,8nm	1 557,9nm
F	Tilt 1	1 563,0nm	1 563,9nm	1 563,0nm	1 562,0nm	1 561,1nm
	Tilt 2	1 567,0nm	1 565,1nm	1 567,0nm	1 568,8nm	1 567,9nm
G	Tilt 1	1 573,0nm	1 573,9nm	1 573,0nm	1 572,0nm	1 571,1nm
	Tilt 2	1 577,0nm	1 575,1nm	1 577,0nm	1 578,8nm	1 577,9nm
H	Tilt 1	1 583,0nm	1 583,9nm	1 583,0nm	1 582,0nm	1 581,1nm
	Tilt 2	1 587,0nm	1 585,1nm	1 587,0nm	1 588,8nm	1 587,9nm

Example of standard stock available WL configurations and their chaining possibilities in one optical channel.
Other WL's on demand