

SAT-02 Single Axis Tiltmeter
Measurement range -15deg. to +15deg., Temperature range -30°C to +80°C

Ordering information			Installation information		
WL configuration	WL type	Nominal WL @ 0deg. @ 22,5°C (after production)	(WL @ -15deg. @ -20°C)	WL @ 0deg. @ 22,5°C	WL @ +15deg. @ +60°C
A	Tilt 1	1 513,0nm	1 511,0nm	1 513,0nm	1 514,9nm
	Tilt 2	1 517,0nm	1 515,0nm	1 517,0nm	1 518,9nm
B	Tilt 1	1 523,0nm	1 521,0nm	1 523,0nm	1 524,9nm
	Tilt 2	1 527,0nm	1 525,0nm	1 527,0nm	1 528,9nm
C	Tilt 1	1 533,0nm	1 531,0nm	1 533,0nm	1 534,9nm
	Tilt 2	1 537,0nm	1 535,0nm	1 537,0nm	1 538,9nm
D	Tilt 1	1 543,0nm	1 541,0nm	1 543,0nm	1 544,9nm
	Tilt 2	1 547,0nm	1 545,0nm	1 547,0nm	1 548,9nm
E	Tilt 1	1 553,0nm	1 551,0nm	1 553,0nm	1 554,9nm
	Tilt 2	1 557,0nm	1 555,0nm	1 557,0nm	1 558,9nm
F	Tilt 1	1 563,0nm	1 561,0nm	1 563,0nm	1 564,9nm
	Tilt 2	1 567,0nm	1 565,0nm	1 567,0nm	1 568,9nm
G	Tilt 1	1 573,0nm	1 571,0nm	1 573,0nm	1 574,9nm
	Tilt 2	1 577,0nm	1 575,0nm	1 577,0nm	1 578,9nm
H	Tilt 1	1 583,0nm	1 581,0nm	1 583,0nm	1 584,9nm
	Tilt 2	1 587,0nm	1 585,0nm	1 587,0nm	1 588,9nm

Example of standard stock available WL configurations and their chaining possibilities in one optical channel.

Other WL's on demand