

**SAT-03 Highly Sensitive Single Axis Tiltmeter**

Measurement range -1.5deg. to +1.5deg., Temperature range -30°C to +80°C

Ordering information			Installation information		
WL configuration	WL type	Nominal WL @ 0deg. @ 22,5°C (after production)	(WL @ +1.5deg. @ -20°C)	WL @ 0deg. @ 22,5°C	WL @ +1.5deg. @ +60°C
A	Tilt 1	1 513,0nm	1 511,0nm	1 513,0nm	1 511,8nm
	Tilt 2	1 517,0nm	1 518,1nm	1 517,0nm	1 519,0nm
B	Tilt 1	1 523,0nm	1 521,0nm	1 523,0nm	1 521,8nm
	Tilt 2	1 527,0nm	1 528,1nm	1 527,0nm	1 529,0nm
C	Tilt 1	1 533,0nm	1 531,0nm	1 533,0nm	1 531,8nm
	Tilt 2	1 537,0nm	1 538,1nm	1 537,0nm	1 539,0nm
D	Tilt 1	1 543,0nm	1 541,0nm	1 543,0nm	1 541,8nm
	Tilt 2	1 547,0nm	1 548,1nm	1 547,0nm	1 549,0nm
E	Tilt 1	1 553,0nm	1 551,0nm	1 553,0nm	1 551,8nm
	Tilt 2	1 557,0nm	1 558,1nm	1 557,0nm	1 559,0nm
F	Tilt 1	1 563,0nm	1 561,0nm	1 563,0nm	1 561,8nm
	Tilt 2	1 567,0nm	1 568,1nm	1 567,0nm	1 569,0nm
G	Tilt 1	1 573,0nm	1 571,0nm	1 573,0nm	1 571,8nm
	Tilt 2	1 577,0nm	1 578,1nm	1 577,0nm	1 579,0nm
H	Tilt 1	1 583,0nm	1 581,0nm	1 583,0nm	1 581,8nm
	Tilt 2	1 587,0nm	1 588,1nm	1 587,0nm	1 589,0nm

Example of standard stock available WL configurations and their chaining possibilities in one optical channel.  
Other WL's on demand